

04/07/2017

Kit Components

Product code	Description
--------------	-------------

G1912	HaloLink™ Resin, 1.25ml
--------------	--------------------------------

Components:

G191	HaloLink™ Resin
------	-----------------

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

1 Identification**Product identifier****Trade name:** HaloLink™ Resin**Article number:** G191**Application of the substance / the mixture** Laboratory chemicals**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Promega Corporation
2800 Woods Hollow Road
Madison, WI 53711
U.S.A.
1-800-356-9526 or (608)-274-4330

Information department: SDS author: Regulatory.Affairs@promega.com**Emergency telephone number:**

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification**Classification of the substance or mixture**

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms** GHS02**Signal word** Warning**Hazard statements**

Flammable liquid and vapor.

Precautionary statements

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

Use explosion-proof electrical/ventilating/lighting/equipment.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 1)

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 2

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 0

Fire = 2

Reactivity = 0

OSHA Hazard Overview (Criteria according to 29CFR1910.1200): Combustible**Primary route(s) of entry:** Oral**Target Organ(s):**

May cause Liver damage (Hepatotoxin)

May affect Nervous system (Neurotoxin)

Other hazards Keep away from sources of ignition.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

* 3 Composition/information on ingredients

Chemical characterization: Mixtures**Description:**

The product is a mixture of the hazardous substances listed below along with unlisted nonhazardous substances. The exact concentration percentages of the hazardous substances may be withheld as a Promega Corp. trade secret.

Dangerous components:

64-17-5 ethanol

10-15%

Additional information: For the wording of the listed risk phrases refer to section 15.

* 4 First-aid measures

Description of first aid measures**After inhalation:** If the patient feels unwell or is concerned, obtain medical advice.**After skin contact:** Generally the product does not irritate the skin.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If the patient feels unwell or is concerned, obtain medical advice.**Information for doctor:****Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Dizziness

Nausea

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

* 5 Fire-fighting measures

Extinguishing media**Suitable extinguishing agents:** Use fire fighting measures that suit the environment.**Special hazards arising from the substance or mixture** None known

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 2)

Advice for firefighters

No special advice

In the case of fire, wear respiratory protective equipment and chemical protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Wear protective clothing.

Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Use only in well ventilated areas.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures: Wash hands before breaks and at the end of work.

Breathing equipment: Not required.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 3)

Protection of hands:

Protective gloves

Select the glove material considering penetration time, rate of diffusion and degradation time.

It is recommended that the selected protective gloves be tested and approved under NIOSH or EU Directive 89/686/EEC and the standard EN 374 derived from it.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:

Safety glasses

Use equipment for eye protection tested and approved under government NIOSH standards.

9 Physical and chemical properties

Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Color:	Colorless
Odor:	Alcohol-like
Odor threshold:	Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	23 - 60 °C (73 - 140 °F)

Flammability (solid, gaseous):	Not applicable.
---------------------------------------	-----------------

Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.

Auto igniting:	Product is not selfigniting.
-----------------------	------------------------------

Danger of explosion:	Product does not present an explosion hazard.
-----------------------------	---

Explosion limits:

Lower:	3.5 Vol %
Upper:	15.0 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44 mm Hg)

Density:	Not determined.
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Solubility in / Miscibility with

Water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.

Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

Organic solvents:	15.0 %
Water:	60.0 %
VOC content:	15.0 %

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 4)

Other information

No further relevant information available.

* 10 Stability and reactivity

Reactivity No further relevant information available.**Chemical stability****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**Possibility of hazardous reactions** No dangerous reactions known.**Conditions to avoid** No further relevant information available.**Incompatible materials:** No further relevant information available.**Hazardous decomposition products:** No dangerous decomposition products known.

* 11 Toxicological information

Information on toxicological effects**Acute toxicity:****LD/LC50 values that are relevant for classification:** No data available**Primary irritant effect:****on the skin:** No irritant effect.**on the eye:** Irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:****Carcinogenic categories****IARC (International Agency for Research on Cancer)**

64-17-5 ethanol

1

NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

* 12 Ecological information

Toxicity**Aquatic toxicity:** Not harmful to the aquatic environment**Persistence and degradability** Not available**Behavior in environmental systems:****Bioaccumulative potential** Not known**Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Not available**Additional ecological information:****General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 5)

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: Handling and Storage and Section 8: Exposure Control/Personal Protection for additional handling information and protection of employees.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number Not hazardous for transportation

DOT, ADR, ADN, IMDG, IATA Void

UN proper shipping name None

DOT, ADR, ADN, IMDG, IATA Void

Transport hazard class(es) None

DOT, ADR, ADN, IMDG, IATA

Class Void

Packing group None

DOT, ADR, IMDG, IATA Void

Environmental hazards:

Marine pollutant: No

Special precautions for user Not applicable.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation": Void

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act):

64-17-5 ethanol

7732-18-5 water

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 6)

Proposition 65**Chemicals known to cause cancer:**

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

64-17-5 ethanol

Carcinogenicity categories**EPA (Environmental Protection Agency)**

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

64-17-5 ethanol

A3

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).**Signal word** Warning**Hazard statements**

Flammable liquid and vapor.

Precautionary statements

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

Use explosion-proof electrical/ventilating/lighting/equipment.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:**Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:

Promega Corporation

Environmental Health and Safety Department

2800 Woods Hollow Road

Madison, WI

Ph: (608)274-4330

Date of preparation / last revision 04/07/2017 / -

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/07/2017

Reviewed on 02/08/2017

Trade name: HaloLink™ Resin

(Contd. of page 7)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

*** Data compared to the previous version altered.**

US