

07/20/2020

Kit Components

| Product code | Description |
|--------------|-------------|
|--------------|-------------|

| | |
|--------------|---|
| G8472 | HaloTag® Alexa Fluor® 660 Ligand |
|--------------|---|

Components:

| | |
|-------|----------------------------------|
| G847A | HaloTag® Alexa Fluor® 660 Ligand |
|-------|----------------------------------|

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

1 Identification**Product identifier****Trade name:** HaloTag® Alexa Fluor® 660 Ligand**Article number:** G847A**Application of the substance / the mixture** For Laboratory Use**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Promega Corporation
2800 Woods Hollow Road
Madison, WI 53711
U.S.A.
1-800-356-9526 or (608)-274-4330

Information department:

SDS author: ChemicalRegulatory@promega.com
Promega Corporation
2800 Woods Hollow Road
Madison, WI 53711
U.S.A.
1-800-356-9526 or (608)-274-4330

Emergency telephone number:

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification**Classification of the substance or mixture**

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS07

Signal word Warning**Hazard-determining components of labeling:**

dimethyl sulfoxide

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 1)

Hazard statements

Harmful if swallowed or in contact with skin.

Precautionary statements

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves / protective clothing.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin: Wash with plenty of water.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 1

Fire = 0

Reactivity = 0

OSHA Hazard Overview (Criteria according to 29CFR1910.1200): Not applicable

Primary route(s) of entry: Oral

Target Organ(s):

Dermal hazard (Cutaneous hazard)

Risk of damage to eyes

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

* 3 Composition/information on ingredients

Chemical characterization: Substances**CAS No. Description**

HaloTag Alexa Fluor 660

Chemical characterization: Mixtures**Description:**

The product is made up of a mixture of non-hazardous components. The exact concentration percentages and components name may be withheld as a Promega Corp. trade secret.

Dangerous components:

| | | |
|---------|--------------------|---------|
| 67-68-5 | dimethyl sulfoxide | 75-100% |
|---------|--------------------|---------|

Additional information: For the wording of the listed risk phrases refer to section 15.

* 4 First-aid measures

Description of first aid measures**General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: If the patient feels unwell or is concerned, obtain medical advice.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 2)

After swallowing: Seek immediate medical advice.

Information for doctor:

Most important symptoms and effects, both acute and delayed

None

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

None known

No further relevant information available.

Advice for firefighters No special advice

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Wear protective clothing.

Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires: The product is not flammable.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: None.

Specific end use(s) No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 3)

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

67-68-5 dimethyl sulfoxide

WEEL Long-term value: 250 ppm

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Protective gloves

Select the glove material considering penetration time, rate of diffusion and degradation time.

It is recommended that the selected protective gloves be tested and approved under NIOSH or EU Directive 89/686/EEC and the standard EN 374 derived from it.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:

Safety glasses

Use equipment for eye protection tested and approved under government NIOSH standards.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

| | |
|------------------------|-----------------|
| Form: | Fluid |
| Color: | Colorless |
| Odor: | Not determined |
| Odor threshold: | Not determined. |

Change in condition

| | |
|-------------------------------------|--------------------|
| Melting point/Melting range: | 18.45 °C (65.2 °F) |
| Boiling point/Boiling range: | Undetermined. |
| Flash point: | Not applicable. |

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 270 °C (518 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 4)

Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapor pressure at 20 °C (68 °F): 2.5 hPa (1.9 mm Hg)

Density at 20 °C (68 °F): 1.1 g/cm³ (9.1795 lbs/gal)

Relative density: Not determined.

Vapor density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with

Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

Organic solvents: 99.7 %

VOC content: 99.66 %

Other information: No further relevant information available.

10 Stability and reactivity

Reactivity: No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials:

Oxidizing agents

Strong acids

Strong reducing agents

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects**Acute toxicity:****LD/LC50 values that are relevant for classification:****67-68-5 dimethyl sulfoxide**

| | | |
|--------------------|-------|------------------------------------|
| Oral | LD50 | 14,500 mg/kg (Rat) |
| Dermal | LD50 | 1,800 mg/kg (Mouse) |
| Irritation of eyes | acute | 500 mg (Rabbit) mild irritation |

Primary irritant effect:

on the skin: No data available.

on the eye: No data available.

Sensitization: No sensitizing effects known.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 5)

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

Toxicity

Aquatic toxicity:

Not available

No further relevant information available.

Persistence and degradability

Not available

No further relevant information available.

Bioaccumulative potential

Not known

No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Not available

Additional ecological information:

General notes: No data available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: Handling and Storage and Section 8: Exposure Control/Personal Protection for additional handling information and protection of employees.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number

Not hazardous for transportation

DOT, ADR, ADN, IMDG, IATA

Not applicable

UN proper shipping name

None

DOT, ADR, ADN, IMDG, IATA

Not applicable

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 6)

| | |
|---|-----------------|
| Transport hazard class(es) | None |
| DOT, ADR, ADN, IMDG, IATA Class | Not applicable |
| Packing group | None |
| DOT, ADR, IMDG, IATA | Not applicable |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Not applicable. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| UN "Model Regulation": | Not applicable |

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act) Inventory:

67-68-5 dimethyl sulfoxide

Hazardous Air Pollutants

None of the ingredients are listed.

Proposition 65

Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenicity categories

EPA (Environmental Protection Agency)

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Signal word Warning

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/20/2020

Reviewed on 07/20/2020

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 7)

Hazard-determining components of labeling:

dimethyl sulfoxide

Hazard statements

Harmful if swallowed or in contact with skin.

Precautionary statements

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves / protective clothing.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin: Wash with plenty of water.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Water hazard class: *Water hazard class 1 (Self-assessment): slightly hazardous for water.*

Chemical safety assessment: *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:

Promega Corporation

Chemical Regulatory Department

2800 Woods Hollow Road

Madison, WI

Ph: (608)274-4330

Date of preparation / last revision *07/20/2020 / 1.0*

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

*** Data compared to the previous version altered.**